


VOLUME 4SUPPLEMENTAL STANDARDS: APPROVED MATERIALS LIST

JUNE 2023



POTABLE WATER AND RECYCLED WATER FACILITIES

ITEM	DESCRIPTION	MANUFACTURER
ADAPTER, FLANGE	4" and larger, mechanical x	Ford FFCA Style
COUPLING	flange. Steel or ductile iron	Romac FCA501, FC400
	construction without anchor	Smith-Blair 912, 913
	pins, epoxy coated, 304	Uni-Flange
	stainless steel bolts and nuts	JCM 301, 303
AIR/VACUUM VALVE	Lightweight plastic with	Pipeline Products- VCAS
ENCLOSURE	integral mounting base and	1424, VCAS 1830
	fastening system. Use	VCDD
	enclosure size as indicated	
	below. 1" and 2" Air Vac Sizes	
	Use: 14" x 24"	
	4" and 6" Air Vac Sizes Use:	
	18" x 30" 6" Air Vac Sizes Use: 24"x36"	
	Yellow for Potable Water	
	Purple for Recycled Water	
AIR VENTS	Air vents for high points in	Armstrong Machine
AHR VENIS	the system, at heat transfer	Works
	coils, and elsewhere as	Bell & Gossett ITT
	required for system air	Hoffman Specialty ITT
	venting	Spirax Sarco
AUTOMATIC FLOW	As required to facilitate	Bell & Gossett ITT
LIMITING BALANCING	system balancing	Flow Design
DEVICES		Griswold
		Kates
BACKFLOW	Approved assemblies per	Wilkins – 975XL2,
PREVENTER -	USC (University of Southern	375XL, 375, 475
DOMESTIC SERVICES	California)	Febco – LF825Y,
		LF825YA, LF860
		Watts – LF009
		Apollo – RPLF4A
BACKFLOW	Approved assemblies per	Wilkins – 975XL,
PREVENTER -	USC (University of Southern	975XL2, 375XL, 375,
IRRIGATION SERVICES	California)	475
		Febco – 825Y, 825YA,
		860, LF825Y,
		LF825YA, LF860
		Watts - 009, LF009
		Apollo – RP4A, RPLF4A

ITEM	DESCRIPTION	MANUFACTURER
BACKFLOW	Approved assemblies per	Wilkins – 350DA,
PREVENTER - FIRE	USC (University of Southern	350ADA, 350ADAR,
SERVICES	California)	350ASTDAR, 450DA,
		450STDA, 450STDAR
		Watts – 709DCDA,
		774DCDA, 757DCDA
		Ames – 3000SS, C300
		Apollo – ALF4AN
BACKFLOW	Approved assemblies per	Wilkins – 375DA,
PREVENTER - COMBO	USC (University of Southern	375ADA, 375ADAR,
SUPPLY WITH FIRE	California)	475DA, 475STDA,
SERVICE		475STDAR,
		3755ASTDAR
		Watts – 909RPDA,
		957RPDA, 994RPDA
		Ames – C500, 5000SS
		Apollo – LF4AN
BLADDER/DIAPHRAGM	Size and number as	Amtrol, Inc
TYPE AIR	indicated; shell constructed	Armstrong Pumps, Inc
ELIMINATION TANKS	of steel per ASME Section	Bell & Gossett ITT
	VIII, Division 1;	Taco, Inc
	bladder/diaphragm	
	constructed of heavy duty	
	Butyl, bladder type to be	
	removable for inspection and	
CASING END SEAL	replacement	Advances Products &
CASING END SEAL	Polyethylene casing spacer, center restrained, position	Systems Cascade
	type with PVC liner and non-	Water Works
	metallic anti-friction runners	Calpico
	metanic anti-metion runners	CCI Products
CASING, SPACER	Polyethylene casing spacer	Advanced Products &
CASING, SI ACER	center restrained position	Systems, INC (APS)
	type with PVC liner and non-	Cascade Water Works
	metallic anti-friction runners	Pipeline Seal & Insulator,
	metanic and metanicis	Inc. (PSI)
		CCI Products
		CCITIOUUCIS

ITEM	DESCRIPTION	MANUFACTURER
COATING	All coatings shall be per EVMWD Standard Specification Section 09800.	Akzo Nobel Carboline Company Sherwin Williams Tnemec Sanchem, Inc. Christy's NO-OX-ID
CORPORATION STOP, MIP X COMPRESSION	Bronze MIP x compression thread ball valve (T-Head only) 1" and 2" full opening	Ford FB110-X-NL Jones E-1935 A. Y. McDonald Mueller Cambridge 301NL
COUPLING	Three part compression coupling (both ends) for 1" and 2" copper pipe	Ford C44-G Series A. Y. McDonald Jones Smith Blair Cambridge 119NL Multi Certainteed Ipex
COUPLING, C900 PVC DEFLECTION	4" through 12" Solid PVC for obtaining deflection only. Provides 5 degree maximum deflection	Any AWWA Compliant
UNIVERSAL BRASS COUPLING	1", 2" brass, compression x compression	Cambridge 119NL U Series
COUPLING, C900 PVC CLOSURE OR REPAIR	4" through 12" solid PVC for closure or repair	Multi Certainteed Ipex Any AWWA Compliant
COUPLING, C905 PVC CLOSURE OR REPAIR	16" through 36" solid PVC for closure or repair	Multi Certainteed Ipex Nyloplast Any AWWA Compliant
COUPLING, FULL CIRCLE REPAIR BAND	Stainless steel full circle repair band. Min 12" width	Romac Ford and Smith Blair
COUPLING, INSULATED, COMPRESSION X	Three part compression insulated coupling (both ends) for 1" copper pipe	A. Y. McDonald 4755DBT Mueller N-35403 Ford Jones

ITEM	DESCRIPTION	MANUFACTURER
COMPRESSION COUPLING, STRAIGHT FLEXIBLE	4" and larger, ductile iron construction, slip x slip, epoxy coated with 304 or 316 stainless steel bolts and nuts. For use on PVC or DI	Ford FCl (Dl) Romac 501 (Dl) Smith-Blair 411(Stl.), 441 (Dl) 442, 461, 462 JCM 210, 215, 241, 242 Romac 501 (Dl), ALPHA
COMPRESSION TANKS	Size and number as indicated; construct of welded carbon steel	Amtrol, Inc Armstrong Pumps, Inc Bell & Gossett ITT Taco, Inc
COUPLING, TRANSITION FLEXIBLE	4" and larger, ductile iron construction, slip x slip, epoxy coated with 304 or 316 stainless steel bolts and nuts. For use on AC, PVC, or DI	Ford FC2A (Dl) Romac 501 (Dl) Smith-Blair 413 (Sti.), 411 (Dl) 441, 442, 461, 462 JCM 212, 241, 242 Romac 501 (Dl), ALPHA
DISMANTLING JOINT	4" and larger steel spigot ASTM A283 Grade C, flange adaptor steel or ductile iron ASTM A536 Grade 65-45- 12	Viking Johnson Smith-Blair 975 JCM 309
DIVERTING FITTINGS	Cast iron body with threaded ends, or wrought copper with solder ends	Amtrol, Inc Armstrong Pumps, Inc Bell & Gossett ITT Taco, Inc
ELL, FIRE HYDRANT BURY, DUCTILE IRON	6" ductile iron bury ells, long radius, FLG x MJ or FLG x FLG	Clow South Bay Foundry Star Pipe Products Sigma SIP Industries
ELL, COMPRESSION TYPE	1" and 2" bronze ell compression x compression for copper pipe	Ford L44-Q Series Jones J-2611 Cambridge 105NL
FIRE HYDRANT, 200 PSI	6" standard 200 PSI wet barrel ductile iron fire hydrant. Epoxy coated interior, shop primed and painted exterior with six-hole bolt pattern	Jones J4040D, J4060D Clow 850, 860

ITEM	DESCRIPTION	MANUFACTURER
FITTING, DUCTILE	Flanged, mechanical, joint or	Pipeline Components
IRON	push-on tees, bends, crosses,	Tyler/Union
	reducers, adapters, etc., for	U.S. Pipe
	water lines 4" and larger.	Star Pipe Products
	Manufactured per AWWA	Sigma
	C110, C111, C153. Double	SIP Industries
	cement mortar lined.	
FLOWMETER	Magnetic flowmeter	McCrometer Ultra Mag
		w/ ProComm
		Converter
GASKET	1/8" thick full ring gasket	NSF 61 Approved
	face aramid fiber bound with	
	nitrile. No asbestos content	
GASKET, RUBBER RING	1/8" thick, rubber ring type,	Calpico
	250 PSI maximum. For 4 "	Johns Manville
	Through 24" pipe flanges.	US Pipe
	For above ground	APS
	applications only.	Garlock Blue-Gard 3000
	Engineering Department	
	approval required.	
JOINT RESTRAINT	360 degree wedge type	Ford Uniflange 1300
ASSEMBLY	restraint system for ductile	Series Ford Uniflange
	iron, C900 PVC, and steel	1500 Series Romac
	pipe, size 4" through 24".	EBAA Iron Smith-Blair
	Joint restraint assembly for	Sigma
	PVC pipe shall have	Star Products
	machined serrations on the	Tyler/Union
	inside diameter.	
LUBRICANT, PIPE	Rubber gasket pipe lubricant	EBAA Iron or Any AWWA
GASKET	for use on PVC or ductile iron	Compliant
	pipe joints, NSF listing	
	required, and AWWA	
	compliant	
METER BOX	19" x 25-½" plastic meter box	Applied Engineering
	& cover for 1" services	#13201G2G
METER BOX	19" x 28-3/4" plastic meter	Applied Engineering
	box and cover for 1-1/2"	#132415P2P
	services	
METER BOX	27-1/4" x 40-1/2" plastic meter	Applied Engineering
	box and cover for 2" services	#173018P2P

ITEM	DESCRIPTION	MANUFACTURER
METER BOX, TRAFFIC	3/4" and 1"	DFW PW5C4-12-4A Star
LID REINFORCED		
FIBERGLASS	1.5" and 2"	DFW PW6C4-12-4A Star
METER STOP, ANGLE	1" bronze angle meter stop	Ford BA43-444W-Q
COMPRESSION X	(ball	Jones J-1963W
METER	valve) with 90 degree lock	Mueller B24258-1
	wing, inlet 110 style	A. Y. McDonald
	compression x outlet swivel	Cambridge 210NL
	meter nut	_
METER STOP, ANGLE	2" bronze angle meter stop	Ford BFA43-777W-Q
COMPRESSION X	(ball valve) with 90 degree	Jones E-1975WSG
METER	lock wing, inlet 110 style	Mueller B-24276N
	compression x flange	A. Y. McDonald
		Cambridge 210NL
METER, WATER	m . 1 .	District to Supply
MORTAR, REPAIR	Two component, lot	Sika top 122,123
	shrinkage, cement based with	STO CR 735, CR 740
	high compressive and	
DIDE CEDITICE	bonding strength	Nr. 11 T
PIPE, SERVICE	1" and 2" type K soft seamless	Mueller Lee
DIDE DUCTHEIDON	tubing, presleeved	Municipex Rehau
PIPE, DUCTILE IRON	For water lines 4" and larger	American Pipe McWane Ductile
	manufactured per AWWA	
	Cl11, C115, C150, C151. Double cement mortar lined	U.S. Pipe
PIPE, PVC C900	For water lines 4" through	Vinyletech
TILE, IVC C900	12" and 8" gate wells. Class	North American Pipe
	150 minimum, and any	Diamond Plastics
	AWWA compliant	Corporation
PIPE, STEEL CEMENT	Steel cylinder, Per AWWA	Ameron
MORTAR LINED AND	M11 and Section 15061. 10	Northwest
COATED (CML&C)	gage minimum wall thickness	TVOTEHWESE
	(special approval required for	
	other fabricators based on	
	experience and quality	
	history).	
POLYETHYLENE	8-mil Thick polyethylene	PE encasement by US
ENCASEMENT	encasement sleeve for ductile	Blue for Potable Water
	iron pipe (DIP) per AWWA C	Purple for Recycled
	105 and recycled PVC,	Water
	CML&C, or DIP non-purple	
	water pipe	

ITEM	DESCRIPTION	MANUFACTURER
PUMP SUCTION	Cast iron body, with threaded	Amtrol, Inc
DIFFUSERS	connections for 2 inch and	Armstrong Pumps, Inc
	smaller, flanged connections	Bell & Gossett ITT
	for 2 1/2 inch and larger	Taco, Inc
		Victaulic
PUMP, VERTICAL		ITT Goulds Pumps
TURBINE		Peerless Pump
		Company Peabody
		Floway
RECYCLED WATER	10"v10" number sign with	American Marsh Troffic Control Systems
SIGN, 18" x 18"	18"x18", purple sign with white letters and a black	Traffic Control Systems
51GN, 16 X 16	symbol on 0.063 aluminum	
	with 3M Eng. Grade	
	reflective sheeting and anti-	
	graffiti coating	
RECYCLED WATER	4" x 8" Duracast plastic sign	"DAS" Curb Marker Part
SIGN, 4" x 8"	with no-slip surface, for	Number CM-ELSIN
	mounting on curbs and	
	sidewalks	
RECYCLED WATER	Weatherproof plastic tag, 3" x	T. Christy Enterprises,
VALVE TAG	4" with permanent black	inc. Part #ID-MAX-
GEDINGE GADDI E EOD	stamped lettering	P2RC007
SERVICE SADDLE FOR	Cast brass ASTM B62 Body with silicone bronze double	Ford 202B
ACP	or stainless steel straps,	Jones J-979 Smith-Blair 323
	outlet sizes 1" and 2"	Mueller
	outlet sizes 1 and 2	Cambridge 810
SERVICE SADDLE FOR	Bronze or brass saddle with	Ford 202BS Jones J-969
PVC C900 AND DI PIPE	stainless steel four bolt	Mueller BR2S Series
	strap(s), thread outlet for	Smith Blair
	sizes 1" and 2" for pipe sizes	Romac 202BS
	4" through 12"	AY McDonald 3846
		Cambridge 812
SERVICE SADDLE FOR	Stainless steel saddle with	Ford FS202 Romac 305
DI PIPE	stained steel thread outlet for	JCM 438
	sizes 1" and 2" for pipe sizes	
TANCENTIALAID	16" and larger	Amtrol Inc
TANGENTIAL AIR SEPARATORS	Perforated stainless steel air	Amtrol, Inc
SEFARATORS	collector tube designed to direct released air into	Armstrong Pumps Bell & Gossett ITT
	compression tank	Taco, Inc
	compression tank	1 aco, 111c

ITEM	DESCRIPTION	MANUFACTURER
TAPPING SLEEVE FOR	Fabricated stainless steel	Romac SST III Power
ACP, CI, DI, AND PVC	tapping sleeve for 4" through	Seal
PIPE	12" hot taps. Stainless steel	Smith-Blair 664/665
	bolts and nuts and full mat	JCM 432
	gasket	
TRACER BOX		Copperhead, Brooks or
		approved equal
VALVE, AIR RELEASE	1" – 2" pressure air release	ARI D-040 or ARI D-060
AND VACUUM RELIEF	and vacuum relief valve,	
	reinforced nylon/compact,	
	rolling seal design. 4" – 6"	
	epoxy coated body, stainless	
	steel trim, compact design.	
	All valves shall be per	
	specification Section 15100.	
VALVE, ANGLE FIRE	For use in recycled water	James Jones J-344 H.P.
PLUG VALVE	blow-off assemblies. All	
	valves shall be per	
	specification Section 15100.	
VALVE, BALL	Bronze, straight,	Ford B44-444-Q, B44-
	compression x compression	777-Q
	for 1" and 2" valves	Jones J-1949SG
	(threaded, both male &	Mueller B-25209
	female). All valves shall be	Cambridge 202NL
	per specification Section	
WALLED DATE	15100.	D ID OVY
VALVE, BALL	2" bronze, straight,	Ford B44- 777 – QW
WITH LOCKING	compression x compression	Jones J-1949SGW
TABS	with locking tabs and brass	Mueller B-25146
(Meter Customer Valve)	handle (threaded both male	AY McDonald 6100 MW
	& female, no locking tabs,	Cambridge 212NL
	S.H.). All valves shall be per	
MAINE DALL	specification Section 15100.	Elip o (C.I.
VALVE, BALL	1" bronze, straight, meter	Ford HB 34S Jones J-
(Meter Customer	swivel, MIP x MIP (purple	1908W Mueller B-
Valve)	handle for recycled water).	24351-1
	All valves shall be per	AY McDonald HB6101M
	specification Section 15100.	Cambridge 212NL

ITEM	DESCRIPTION	MANUFACTURER
VALVE, BREAK-OFF CHECK	Break-off check valve for fire hydrants. Use when indicated on Approved Plans. All valves shall be per specification Section 15100.	Long Beach LB 400 Avk Flow guard II
VALVE, BUTTERFLY	16" and larger, A WW A C504, Class. All valves shall be per specification Section 15100. B. Thermosetting for fusion bonded epoxy coated and lined (150 psi max), seat in the body, FLG x FLG	Mueller Lineseal III M&H Pratt Groundhog DeZurik BAW *Crispin K-Flow
VALVE, CALIBRATED BALANCING	Calibrated ball valve. All valves shall be per specification Section 15100.	Bell & Gossett ITT Taco, Inc Griswold Flow Design
VALVE, DIAPHRAGM ACTUATED CONTROL VALVE	Hydraulically actuated diaphragm type control valves. All valves shall be per specification Section 15100.	Cla-Val Automatic Control Valve
VALVE, GATE, RESILIENT WEDGE (RWGV)	4" through 12" non-rising low zinc bronze or stainless steel stem, ductile or cast iron body and bonnet, encapsulated wedge per AWWA C509 or C515 with epoxy coated interior. Manufactured to AWWA C509 or C515, FLG x FLG. All valves shall be per specification Section 15100.	American FC, Series 2500 Clow M&H Mueller
VALVE, GLOBE	Brass globe valves. All valves shall be per specification Section 15100.	Crane 1 or 2
VALVE, INSULATED BALL	1" bronze, straight, compression x compression, insulated type. All valves shall be per specification Section 15100.	Mueller N-35209 Cambridge 301NL- M4HI4

ITEM	DESCRIPTION	MANUFACTURER
VALVE, LOCKABLE	3/4" and 1" bronze customer	Ford B13-332W w/ HT34
BALL	shutoff (ball valve), inlet FIP	B13-444W w/ HT34
	x compression, lockable tabs,	Jones J-1908W, J-1900W
	with lever handle. All valves	Cambridge 212NLH
	shall be per specification	
	Section 15100.	
VALVE, LOCKABLE	1-1/2" and 2" Bronze	Ford BF13-666W w/ HB-
BALL	customer shutoff (ball valve),	67S,
	inlet FIP x compression,	BFI3- 777W w/HB-67S
	lockable tabs, with lever	Jones J-1913W
	handle. All valves shall be per	Cambridge 212NLH
WALVE DDECOUDE	specification Section 15100.	Cla Val agC at
VALVE, PRESSURE REDUCING	For water main pressure reducing, 4" through 16". All	Cla-Val 90G-01
REDUCING	valves shall be per	
	specification Section 15100.	
VALVE, PRESSURE	For service connections, 3/4"	Wilkins
REGULATING	/ 1". All valves shall be per	Watts
REGULATING	specification Section 15100.	Febco
VALVE, PUMP	Non-slam check valve with	Amtrol, Inc
MULTIPURPOSE	spring loaded weighted disc,	Armstrong Pumps, Inc
	and calibrated adjustment	Bell & Gossett ITT
	feature to permit regulation	Taco, Inc
	of pump discharge flow and	·
	shutoff. All valves shall be	
	per specification Section	
	15100.	
VALVE, SAFETY RELIEF	Valve body shall be cast iron,	Amtrol, Inc
	with all wetted internal	Bell & Gossett ITT
	working parts made of brass	Taco, Inc
	and rubber. All valves shall	
	be per specification Section	
TALLE MARED	15100.	Cla Val
VALVE, WATER	Globe type ductile iron body	Cla-Val
PRESSURE CONTROL	valve. All valves shall be per	
VALVE, WELL LID	specification Section 15100. Ductile iron machined frame.	South Pay
VALVE, WELLLID		South Bay
	See standard drawings for markings	
	markings	

ITEM	DESCRIPTION	MANUFACTURER
WALL FANS	Fans with motors, drives, guards, vibration isolation and coatings, suitable for installations exposed to the weather	Greenheck
WATER SAMPLING POINT ASSEMBLY	Water sampling station with sampling valve as well as full flow flushing valve, complete with aluminum enclosure	American-MC Model EZ- 01F or approved equal
WARNING/ IDENTIFICATION TAPE	6" wide, warning/identification (non- metallic) marking tape for buried facilities	Calpico, Type 1 Line-Tec, Type B Thor, Elast Tec Northtown Dot Sales
WIRE, TRACER	#10 AWG solid copper UF Type wire, with cross linked polyethylene insulation. Blue in color	Cosberg Industries Paige Baron Copperhead Industries Regency Wire & Cable
	Epoxy, for use in split bolt connector	3M Scotch Coat 306

SEWER FACILITIES

FOR USE ON NEW CONSTRUCTION OF SEWER FACILITIES

ITEM	DESCRIPTION	MANUFACTURER
AIR COMPRESSOR	SX 7.5 T compressor with 125.0 psig, 60 Hz screw compressors and an integrated dryer	Kaeser Compressors
CASING, END SEAL	1/4" thick styrene butadiene rubber sheet end seal. Use 1" wide stainless steel bands	Advanced Products & Systems Cascade Water Works Calpico CCI Products
CASING, SPACER	Polyethylene casing spacer center restrained position type with PVC Liner and non-metallic anti- friction runners	Advanced Products & Systems, Inc (APS) Cascade Water Works Pipeline Seal & Insulator, Inc. (PSI) CCI Products
CLEANOUT BOX	Traffic and non-traffic rated. Use 6" cleanout box for 4" lateral and 10" cleanout box for 6" or larger lateral	JR Concrete Applied Engineering
DAMP-PROOFING	Coating systems used on the exterior surface of manholes at and below water table	Kop-Coat, Bitumastic Super Service Black
FLOWMETER	Magnetic flowmeter	Krohne Optiflux w/ IFC- 100 Converter
MANHOLE, CAST IRON FRAME AND COVER	30" nominal diameter cast iron frame and covers per ASTM A48, Class 35B, with machined seats.	Alhambra Foundry National Casting Neenah South Bay Foundry
MANHOLE. COMPOSITE FRAME AND COVER	24" fiber reinforced polymer cover and frame assembly with two (2) quarter turn paddle locks. For manhole applications outside of the right of way	EJ Co. 2600 Series Product Number NPR21-003111-30145, or Equal

FOR USE ON NEW CONSTRUCTION OF SEWER FACILITIES

ITEM	DESCRIPTION	MANUFACTURER
MANHOLE, COATING	Spray-on epoxy coating or	Raven Lining Systems Inc.
	polyurethane lining	Sprayroq
		Zebron
		Sauereisen
		Sherwin-Williams Dura-
		Plate 6100
		Utilithane
MANHOLE, JOINT	Pre-formed, cold applied,	Ramnek or Equal
SEALANT	adhesive, rope-like, butyl	
	rubber gasket to form a	
	water tight seal between	
	manhole sections	
MANHOLE, PIPE	Rubber o-ring type gasket	Indiana Seal Company
CONNECTOR	for pipe to manhole	Fernco
	connection for cast-in-	Press Seal
	place manholes and	GPK
	cemented-in- place	
	connections (for existing	
MANUAL E DIDE	manholes)	7.74.03
MANHOLE, PIPE	Rubber flexible type	J-M Pipe
CONNECTOR	connector for pipe to	PW Pipe
	manhole connection for	
MANUOLE DOLVMED	precast manholes	Armorock LLC
MANHOLE, POLYMER CONCRETE	Access manholes for sewer	Monoform Plus
CONCRETE	mains (grade rings, cones,	Monotoriii Pius
MANHOLE DDECAST	risers, and bases) Access manholes for sewer	Old Castle
MANHOLE, PRECAST CONCRETE	mains (grade rings, cones,	Southwest
CONCRETE	risers, and bases) designed	Jensen
	for H-20 highway loading	JR Concrete
	101 11-20 ingnway loading	MCS, Inc.
		Manhole Builders
PIPE, PVC	4" - 8"ASTM D	Vinyltech
11111,110	3034, SDR35	Lamson Vylon
	8"- 15" SDR26	North American Pipe
	18" through 24" PS 115 PVC	Diamond Plastics
	>24" District approval	Corporation
	District approvar	Jorporation

FOR USE ON NEW CONSTRUCTION OF SEWER FACILITIES

ITEM	DESCRIPTION	MANUFACTURER
PUMPS, SUBMERSIBLE	Vortex or non-clog with 460 volt, 3-Phase, 60 Hz premium efficiency motor	ESSCO
	To be used when there is a ragging issue	Cornell (Delta Style Impeller)
SADDLE	4" and 6" wye and tee connections for sewer line installations	Multi Inserta Tee GPK
SERVICE SADDLE DI PIPE	Stainless steel saddle with stained steel thread outlet for sizes 1" and 2"	Ford FS202 Romac 305 JCM 438
VALVE, AIR RELEASE AND VACUUM RELIEF	Pressure Air release and vacuum valve, composite body, polymer and stainless-steel operating parts. All valves shall be per specification section 15100.	ARI D-025 or ARI D-26
VALVE, BACKWATER	4" extendable ABS valve. All valves shall be per specification section 15100.	Clean Check, Inc. Mainline Backflow Products Inc.
WALL FANS	Fans with motors, drives, guards, vibration isolation and coatings, suitable for installations exposed to the weather	Greenheck
WARNING/ IDENTIFICATION TAPE	Warning/identification tape 6" wide, colored green, with continuous warning "CAUTION: SEWER LINE BURIED BELOW"	Calpico, Type 1 Line-Tec, Type B Thor, Elast Tec Northtown Dot Sales

APPROVED PAINT COLORS

LIST OF APPROVED PAINT COLORS

ITEM	COLOR	MANUFACTURER
ABOVEGROUND FACILITY	Beige (RGB 209 / 199 /	Sherwin Williams
PIPING, VALVES, AND	184)	SW7036
APPURTENANCES		
BACKFLOW PREVENTION	Safety Blue	
ASSEMBLY, POTABLE WATER		
BACKFLOW PREVENTION	Pantone Purple	Pantone
ASSEMBLY, RECYCLED WATER	_	
BOLLARD/GUARD POST	Osha Yellow	
ENCLOSURE FOR POTABLE	Osha Yellow	
WATER MAINS		
ENCLOSURE FOR RECYCLED	Pantone Purple	Pantone
WATER MAINS	_	
FIRE DOUBLE DETECTOR	Safety Red	
CHECK METER INSTALLATION	-	
FRP SAFETY LADDER	Safety Yellow	
MARKER POST, POTABLE	Safety Blue	
MARKER POST, SEWER	Forest Green	
MARKER POST, RECYCLED	Pantone Purple	
MARKER POST, GATE WELL	White	
POTABLE WATER 8" VALVE	Safety Blue Enamel	Sherwin Williams
WELL CAP W/ 4" SKIRT		Grainger
POTABLE WATER METER BOX -	Forest Green	
(METER READING BOLT		
DOWN, BOLT DOWN, AND		
METER READING CAPTIVE L-		
BOLT DOWN)		
PRV, POTABLE	Safety Blue	
PRV, RECYCLED	Pantone Purple	
RECYCLED WATER SIGNS AND	Pantone Purple	Pantone
VALVE TAGS		
RECYCLED WATER PIPES AND	Pantone Purple	Pantone
APPURTENANCES		
SAMPLING COVER, POTABLE	Osha Yellow	
SAMPLING COVER, RECYCLED	Pantone Purple	Pantone
TEMPORARY POTABLE WATER	Pantone Purple	Pantone
TO RECYCLED WATER INTER-		
CONNECTION		
WATER METER, ABOVE	Safety Blue	
GRADE, POTABLE		
WATER METER, ABOVE	Pantone Purple	Pantone
GRADE, RECYCLED		

PIPE IDENTIFICATION TABLE

PIPE IDENTIFICATION TABLE

TYPE OF PIPE	PIPE USE	COLOR
WATER LINES	RAW WATER	Dark Green
	SETTLED/CLARIFIED	Aqua
	WATER	
	POTABLE WATER	Dark Blue
	RECYCLED WATER	Purple
CHEMICAL LINES	ALUM OR PRIMARY	Orange
	COAGULANT	
	AMMONIA	White
	CARBON SLURRY	Black
	CAUSTIC	Yellow w/ Green Band
	CHLORINE GAS OR	Yellow
	SOLUTION	
	FLUORIDE	Light Blue w/ Red Band
	LIME SLURRY	Light Green
	OZONE	Yellow w/ Orange Band
	PHOSPHATE	Light Green w/ Red Band
	COMPOUNDS	
	POLYMERS OR	Orange w/ Green Band
	COAGULANT AIDS	
	POTASSIUM	Violet
	PERMANGANATE	
	SODA ASH	Light Green w/ Orange Band
	SULFURIC ACID	Yellow w/ Red Band
	SULFUR DIOXIDE	Light Green w/ Yellow
		Band
WASTE LINES	BACKWASH WASTE	Light Proven
		Light Brown
	SLUDGE DAIALAMA CEEVALATEED	Dark Brown
	RAW WASTEWATER	Dark Gray
OTHER LINES	COMPRESSED AIR	Dark Green
	NATURAL GAS	Red
	METHANE GAS	Orange